

## Han® 4A — Plastic Version

### Han-Kit® -4AGK


 Panel Cutout  
22 × 22 mm

Han-Kit® -4AGK	
Hood <sup>1)</sup>	Han® 3 A straight
Bulkhead mounted house <sup>1)</sup>	Han® 3 A straight
Material	Plastic
Protection degree <sup>2)</sup>	IP67
Cable gland	M20, plastic
Cable diameter	5-9 mm/6-12 mm
Insert	Han® 4 A, 4-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	10 A 230/400 V 4 kV 3
Rated voltage conductor-ground	
Rated voltage conductor-conductor	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103907	10 20 004 0002	Han-Kit® 4A, Plastic, 4 Poles + Ground, Top-Entry Plastic Hood, Straight Bulkhead Mount Housing	59.39	53.98

## Han-Kit® -4AWK


 Panel Cutout  
22 × 22 mm

Han-Kit® -4AWK	
Hood <sup>1)</sup>	Han® 3 A straight
Bulkhead mounted house <sup>1)</sup>	Han® 3 A angled
Material	Plastic
Protection degree <sup>2)</sup>	IP67
Cable gland	M20, plastic
Cable diameter	5-9 mm/6-12 mm
Insert	Han® 4 A, 4-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	10 A 230/400 V 4 kV 3
Rated voltage conductor-ground	
Rated voltage conductor-conductor	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103908	10 20 004 0004	Han-Kit® 4A, Plastic, 4 Poles + Ground, Top-Entry Plastic Hood, Right-Angle Bulkhead Mount Housing	62.95	57.22

## Han-Kit® -10A


 Panel Cutout  
24 × 57 mm

Han-Kit® -10 A	
Hood <sup>1)</sup>	Han® 10 A
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M20, metal
Cable diameter	5-9 mm/6-12 mm
Insert	Han® 10 A, 10-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 250 V 4 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103909	10 20 010 0000	Han-Kit® 10A Kit, Metal, 10 Poles + Ground, Side-Entry Metal Hood, Straight Bulkhead Mount Housing	98.86	89.88


## Han-Kit® -16A


 Panel Cutout  
24 × 57 mm

Han-Kit® -16 A	
Hood <sup>1)</sup>	Han® 16 A
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M20, metal
Cable diameter	5-9 mm/6-12 mm
Insert	Han® 16 A, 16-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 250 V 4 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103910	10 20 016 0000	Han-Kit® 16A Kit, Metal, 16 Poles + Ground, Side-Entry Metal Hood, Straight Bulkhead Mount Housing	97.80	93.29


## Han-Kit® -6B


 Panel Cutout  
35 × 48 mm

Han-Kit® -6 B	
Hood <sup>1)</sup>	Han® 6 B
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M20, metal
Cable diameter	5-9 mm/6-12 mm
Insert	Han® 6 E, 6-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 500 V 6 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103911	10 33 006 0000	Han-Kit® 6B Kit, Metal, 6 Poles + Ground, Side-Entry Metal Hood, Straight Bulkhead Mount Housing	54.71	52.60


## Han-Kit® -10B


 Panel Cutout  
35 × 60 mm

Han-Kit® -10 B	
Hood <sup>1)</sup>	Han® 10 B
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M25, metal
Cable diameter	5-16 mm/13-18 mm
Insert	Han® 10 E, 10-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 500 V 6 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103912	10 33 010 0000	Han-Kit® 10B, Metal, 10 Poles + Ground, Side-Entry Metal Hood, Straight Bulkhead Mount Housing	69.82	66.60


## Han-Kit® -16B


 Panel Cutout  
35 × 82 mm

Han-Kit® -16 B	
Hood <sup>1)</sup>	Han® 16 B
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M32, metal
Cable diameter	13-20 mm/18-25 mm
Insert	Han® 16 E, 16-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 500 V 6 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103915	10 33 016 0000	Han-Kit® 16B Kit, Metal, 16 Poles + Ground, Side-Entry Metal Hood, Straight Bulkhead Mount Housing	101.61	91.09

## Han-Kit® -24B


 Panel Cutout  
35 × 108 mm

Han-Kit® -24 B	
Hood <sup>1)</sup>	Han® 24 B
Material	Die cast aluminium alloy
Protection degree <sup>2)</sup>	IP65
Cable gland	M32, metal
Cable diameter	13-20 mm/18-25 mm
Insert	Han® 24 E, 24-pins + GND
Screw terminal	1-2.5 mm AWG 18-14
Electrical data according to DIN EN 61 984 <sup>3)</sup>	
Rated current	16 A 500 V 6 kV 3
Rated voltage	
Rated impulse voltage	
Pollution degree	
Rated voltage according to UL/CSA:	600 V

Stock No.	Mfr.'s Type	Description	EACH	
			1-4	5-9
70103916	10 33 024 0000	Han-Kit® 24B Kit, Metal, 24 Poles + Ground, Side-Entry Metal Hood, Right-Angle Bulkhead Mount Housing	103.32	99.89

1) Bulkhead mounted housing with flange gasket. 2) Protection degree acc. to DIN EN 60 529 in locked position. 3) For use only in grounded circuits.